

POWEROIL SAPPHIRE H 38 (LOW PCA OIL)

POWEROIL SAPPHIRE H 38 is Medium viscosity rubber processing oil, it meets European Regulation (EU directive 2005/69/EC) for Nontoxic and Non Carcinogenic Oils of < 3 % PCA Content as per IP: 346 Standard and are PAH free. It is also compatible for processing NR, SBR, PBR, EPDM and Reclaim Rubber.

Sr No	Characteristics	Unit	Test Method	Specification	
				Min	Max
1	Appearance	-	Visual	Clear Liquid	
2	Color, ASTM	-	ASTM D 1500	-	4.0
3	Density at 15°C	gm/ml	ASTM D 1298	Report	
4	Density at 29.5°C	gm/ml	ASTM D 1298	0.900	0.950
5	Kinematic Viscosity at 40°C	cSt	ASTM D 445 / D 7042	360	400
6	Flash Point, (COC)	° C	ASTM D 92	240	-
7	Pour Point	° C	ASTM D 97	-	-9
8	Aniline Point	° C	ASTM D 611	95	105
9	DMSO Extract (PCA Content)	%	IP 346	-	3.0
10	Poly Aromatic Hydrocarbons (PAH'S), sum of 24 PAH	mg/kg	BS EN 16143	-	10

Application:

Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility. Website: www.apar.com

Product Data Sheet
 Version 1, 1st January, 2024

- Manufacturing of Tyres
- Retreads
- Reclaim Rubber
- Extrusion Profiles
- Molded / Extruded Products