

Petroleum Specialities FZE Wholly owned subsidiary of Apar Industries Itd. Powering Ahead



POWEROIL PEARL H 400

Meets the requirements of following Specifications:

- EP (Current Revision), Liquid Paraffin.
- BP (Current Revision), Liquid Paraffin.
- US FDA 21 CFR 172.878 & 21 CFR 178.3620 (a), White Mineral Oil.

Sr	Characteristics	Unit	Test	Specification	
No	Cital acteristics		Method	Min.	Max.
1	Appearance	-	Visual	Colourless, transparent, oily liquid,	
				free from florescence in daylight.	
2	Solubility	-	EP / BP	Practically insoluble in water, slightly	
				soluble in ethanol (96%) and miscible with hydrocarbons.	
3	Color, Saybolt	-	ASTM D 156	+ 30	-
4	Kinematic Viscosity at 40°C	cSt	ASTM D 445	75.0	80.0
			ASTM D 7042		
5	Dynamic Viscosity at 20°C	mPas	EP / BP	200	230
6	Flash Point, (COC)	° C	ASTM D 92	200	-
7	Pour Point	° C	ASTM D 97	•	-9
8	Relative Density at 20°C	-	EP / BP	0.845	0.890
9	Acidity or Alkalinity	-	EP / BP	Not more than 0.1 ml of	
,				0.1 M NaOH	
10	Readily Carbonisable	_	EP / BP	Pass	
	Substances		21 / 21		
11	Solid Paraffin	-	EP / BP	Pass	
12	Polycyclic Aromatic		EP / BP	Pass	
12	Hydrocarbon	_	EF / DF	Fd	155





POWEROIL PEARL H 400 (Liquid Paraffin - EP) is a high purity EP / BP grade white mineral oil formulated from highly refined hydrotreated base oils meeting the extreme purity requirements of the European Pharmacopoeia and British Pharmacopoeia which ensures the absence of any significant sulfur, nitrogen, oxygen and halogen derivatives, unsaturated substances and aromatics

Application: Used in applications which includes medical formulations, ointments, laxatives, repository vaccines, hair oils, hair creams, cosmetics, facial creams and lotions, gelatin capsules, protective coatings for fruits and vegetables, veterinary preparations, egg preservatives etc.