

## Petroleum Specialities FZE Wholly owned subsidiary of Apar Industries Itd.



## **POWEROIL PEARL H 500**

Meets the requirements of following Specifications:

- USP/NF (Current Revision), Mineral oil..
- US FDA 21 CFR 172.878 & 21 CFR 178.3620 (a), White Mineral Oil.

Sr	Characteristics	Unit	Test Method	Specification	
No				Min.	Max.
1	Description	-	Visual	Colourless, transparent , oily	
				liquid , free from florescence in	
				daylight.	
2	Color, Saybolt	-	ASTM D 156	+ 30	-
3	Kinematic Viscosity at 40°C	cSt	ASTM D 445	90	110
			ASTM D 7042		
4	Flash Point, (COC)	° C	ASTM D 92	220	-
5	Pour Point	° C	ASTM D 97	-	-9
6	Specific Gravity at 25°C	-	USP	0.845	0.905
7	Acidity	-	USP	Not more than 1 ml of	
				0.01 N NaOH	
8	Readily Carbonisable	_	USP	Pass	
	Substances		031		
9	Polycyclic Aromatic	_	USP	Pass	
	Hydrocarbon	•	031		
10	Solid Paraffin	-	USP	Pass	
11	Sulfur Compounds	-	USP	Pass	

**POWEROIL PEARL H 500** (Mineral Oil-USP) is a high purity USP grade white mineral oil formulated from highly refined hydrotreated base oils meeting the extreme purity requirements of the United State Pharmacopoeia which ensures the absence of any significant sulfur, nitrogen, oxygen and halogen derivatives, unsaturated substances and aromatics



## Petroleum Specialities FZE Wholly owned subsidiary of Apar Industries Itd.



**Application:** Used in applications which includes medical formulations, ointments, laxatives, repository vaccines, hair oils, hair creams, cosmetics, facial creams and lotions, gelatin capsules, protective coatings for fruits and vegetables, veterinary preparations, egg preservatives etc.