

**POWEROIL TOPAZ H 500**

Meets the requirements of US FDA 21 CFR 178.3620 (b).

Sr No	Characteristics	Unit	Test Method	Specification	
				Min	Max
1	Appearance	-	Visual	Transparent, colourless, bright and clear oily liquid.	
2	Color, Saybolt	-	ASTM D 156	+25	-
3	Density at 25°C	gm/ml	ASTM D 1298	0.845	0.880
4	Kinematic Viscosity at 40°C	cSt	ASTM D 445 / D 7042	90.0	110.0
5	Flash Point, (COC)	° C	ASTM D 92	220	-
6	Pour Point	° C	ASTM D 97	-	-9

**POWEROIL TOPAZ H 500** (TECHNICAL GRADE WHITE OIL) is a light white oil formulated from highly refined hydrotreated base oils which is colorless, tasteless and odorless.

It meets US FDA 21 CFR 178.3620 (b) requirements for (+25) Saybolt color & UV absorbance.

**Application:** **POWEROIL TOPAZ H 500** is suitable for use in processes/products requiring clear white oils. These oils find extensive usage in textile processing ( non staining lubrication ) , incense & perfume manufacture, plastic, paper and cosmetic industries, several oil based formulations, hair oils, hair lotions, shoe polish and petroleum jelly manufacturing industries.

**Performance Benefits :** Excellent oxidation resistance



Tomorrow's solutions today

**Petroleum Specialities FZE**

Wholly owned subsidiary of Apar Industries Ltd.

**POWEROIL®**

Powering Ahead

High film strength

Non staining

Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility. Website: [www.apar.com](http://www.apar.com)

**Product Data Sheet**  
Version # 1, 1<sup>st</sup> January, 2024